## § 57.205 Submission of supplementary information upon relaxation of an SO<sub>2</sub> SIP emission limitation.

(a) In the event an  $SO_2$  SIP limit is relaxed subsequent to EPA approval or issuance of a second period NSO, the smelter issued the NSO shall submit to the issuing agency and EPA such supplementary information that EPA considers appropriate for purposes of determining whether the means of compliance with the new SIP limit are adequately demonstrated to be reasonably available under the financial eligibility tests specified in §57.102(b)(3). The smelter shall submit such information within sixty days of notification by EPA. This time limit may be extended by EPA for good cause.

(b) Upon receipt of any supplementary information required under paragraph (a), the issuing agency shall promptly reevaluate the availability of the means of compliance with the new SIP limit under the NSO eligibility tests specified in §57.102(b)(3). If the issuing agency determines that the demonstrated control technology necessary to attain the new SO<sub>2</sub> SIP limit is adequately demonstrated to be reasonably available under the eligibility tests, so as to permit the smelter to comply with the new SIP limit on or before January 1, 1988, the NSO shall be amended within the time contemplated by §57.202(a) after receipt of the supplementary information. Such amendment shall require compliance with the new  $SO_2$  SIP limit as expeditiously as practicable in accordance with §57.201(d)(3). The issuing agency, if not EPA, shall promptly submit its determination and any necessary NSO amendments to EPA.

- (c) EPA shall take action to approve or disapprove the issuing agency's determination and NSO amendment, if any, within a reasonable time after receipt of such determination and amendment.
- (d) If EPA disapproves the issuing agency's determination or NSO amendment, or if a smelter fails to submit any supplementary information as required under paragraph (a), EPA and/or the issuing agency shall take appropriate remedial action. EPA shall take appropriate remedial action if the issuing agency does not make any de-

termination and amendment required by this section within the time contemplated by §57.202(a).

## Subpart C—Constant Controls and Related Requirements

## § 57.301 General requirements.

Each NSO shall require an interim level of sulfur dioxide constant controls to be operated at the smelter, unless a waiver of this requirement has been granted to the owner under subpart H of this part. Except as otherwise provided in \$57.304, the interim constant controls shall be properly operated and maintained at all times. The NSO shall require the following gas streams to be treated by interim constant controls:

- (a) In copper smelters, off-gases from fluidized bed roasters, flash furnaces, NORANDA reactors, electric furnaces and copper converters;
- (b) In lead smelters, off-gases from the front end of the sintering machine and any other sinter gases which are recirculated;
- (c) In zinc smelters, off-gases from mult-hearth roasters, flash roasters and fluidized bed roasters; and
- (d) In all primary nonferrous smelters, all other strong SO<sub>2</sub> streams.
- (e) In all primary nonferrous smelters, any other process streams which were regularly or intermittently treated by constant controls at the smelter as of August 7, 1977.

## § 57.302 Performance level of interim constant controls.

(a) Maximum feasible efficiency. Each NSO shall require: that the smelter operate its interim constant control systems at their maximum feasible efficiency, including the making of any improvements necessary to correct the effects of any serious deficiencies; that the process and control equipment be maintained in the way best designed to ensure such operation; and that process operations be scheduled and coordinated to facilitate treatment of process gas streams to the maximum possible extent. Maximum feasible efficiency shall be expressed in the NSO in the form of a limitation on the concentration of SO2 in the tail gas of each individual control system in combination